


LA400PKGUL 24VDC RESIDENTIAL LINEAR ACTUATOR

Our most popular swing gate operator for residential applications.



PRODUCT HIGHLIGHTS

BATTERY BACKUP

Provides up to 400 Cycles or 97 Days of Standby Power

myQ® TECHNOLOGY

Allows You to Securely Monitor and Control Your Gate Operator from Anywhere with the myQ App

RELIABLE

COMMERCIAL-DUTY CAST-ALUMINUM HOUSING WITH HEAVY-DUTY DC MOTOR PERFORMS IN THE MOST DEMANDING APPLICATIONS.

SMOOTH START/STOP OPERATION AND MID-TRAVEL REVERSAL EXTEND HARDWARE LIFE OF THE GATE AND OPERATOR.

BATTERY BACKUP PROVIDES SEAMLESS ACCESS BY PROVIDING STANDBY POWER WHEN THE POWER IS DOWN.

SURGE SUPPRESSION PROVIDES INDUSTRIAL SURGE AND LIGHTNING PROTECTION AGAINST STRIKES UP TO 50 FEET AWAY.

WARRANTY 2 YEARS.

SMART

myQ TECHNOLOGY ENABLES YOU TO SECURELY CONTROL AND MONITOR YOUR GATE OPERATOR FROM ANYWHERE.*

WIRELESS DUAL-GATE COMMUNICATION SYNCHRONIZES GATE OPENING/CLOSING AND ELIMINATES EXPENSIVE DRIVEWAY TRENCHING COSTS (REQUIRES SECOND CONTROL BOX).

BI-PART DELAY MONITORS AND ADJUSTS SPEED AND POSITION OF EACH WING TO ENSURE PRIMARY GATE CLOSES LAST.

PARTY PASS ALLOWS FOR THE GATES TO BE HELD OPEN FOR AN EXTENDED PERIOD OF TIME.

SOLAR-READY, ULTRA-RELIABLE SYSTEM DELIVERS POWER WHEN AND WHERE YOU NEED IT MOST.

SAFE AND SECURE

SECURITY+ 2.0® SAFEGUARDS ACCESS WITH AN ENCRYPTED TRI-BAND SIGNAL TO VIRTUALLY ELIMINATE INTERFERENCE AND OFFER EXTENDED RANGE.

INHERENT REVERSING SENSOR DETECTS OBSTRUCTIONS AND REVERSES GATE WHEN CLOSING OR STOPS/REVERSES THE GATE WHEN OPENING.

FIRE DEPARTMENT COMPLIANCE ALLOWS GATE TO AUTO-OPEN UPON LOSS OF AC POWER OR BATTERY DEPLETION.

MANUAL DISCONNECT WHEN UNLOCKED ALLOWS GATE TO BE OPENED MANUALLY.

UL® LISTED GATE OPERATORS WITH MONITORED SAFETY ENTRAPMENT PROTECTION DEVICES.

*Cellular data or Wi-Fi® connection required. Test equipment regularly and follow safety instructions.

INCLUDED ACCESSORIES:

MONITORED RETRO-REFLECTIVE PHOTO EYE

Enhanced retro-reflective photo eye now with heater and wider beam, engineered to stay aligned; max. range: 50 ft.



LMRRL

SAFETY ADD-ONS:

MONITORED THROUGH-BEAM PHOTO EYES

Enhanced through-beam now with wider beam and heater for high performance in most environments; max. range: 90 ft.



LMTBUL

MONITORED WIRELESS EDGE KIT

Low-energy Bluetooth® connection between a LiftMaster Monitored Resistive Edge and the gate operator; max. range: 130 ft.**



LMWKITU

MONITORED SAFETY ENTRAPMENT EDGES

Full line of Small, Large and Wraparound Profile Edges that sense obstructions.



EDGES

TOTAL SOLUTION ACCESSORIES:

WIRELESS COMMERCIAL KEYPAD

Provides constant pressure override to control gate operator if safety devices fault yet are free of obstructions. Hold Open/Party Pass enabled with gate operator firmware 4.2 or higher.



KPW5

INTERNET GATEWAY

Connects myQ-enabled gate operators to the Internet and enables control through the myQ App.



828LM

SOLAR PANEL KIT

Uses the sun to power the operator with (2) 10W or (2) 20W solar panels.



210W/220W

**Wireless kit for up to 4 transmitters and 2 resistive edges per transmitter.

MASTERFUL ENGINEERING.

MECHANICS



- **24VDC** Continuous-Duty Motor
- **Operator Duty Rating:** 100 Cycles per Day
- **Wormgear Reduction:** Precision-Machined All-Metal Gear Drive

POWER



- **115V** Single-Phase (Standard Control Box)
- **Solar-Ready, Ultra-Reliable System** Delivers Power When and Where You Need It (LMRRUL/LMTBUL Heater Option Not Recommended for Solar Applications)
- **Accessory Power:** 24VDC 500mA Output

COMMERCIAL-GRADE DESIGN




- **Housing:** Commercial-Duty Cast Aluminum
- **UL® Usage Classification:** I, II, III and IV
- **Weights:**
Actuator Arm: 19 lbs.
Standard Control Box: 13 lbs.
(Includes [2] 7Ah Batteries)

BATTERY BACKUP OPERATION

Battery	Cycles	Standby Time
(2) 7Ah	400	97 Days
(2) 33Ah	3,622	180 Days

(Cycles and Standby Time Based on Stand-Alone System)

RECOMMENDED CAPACITIES



LA400CONTUL



LA400DC

XLSOLARCONTUL

[NOT INCLUDED]

21.00" x 17.22" x 6.19"

TEMPERATURE SPECIFICATIONS

- 4°F (-20°C) to 140°F (60°C)



GATE TRAVEL SPEED
Opens 90° in 15–17 Seconds

STANDARD FEATURES.

SYNCHRONIZED CLOSE

- Simultaneously Closes Gates

MONITORED SAFETY INPUTS

- 3 Main Board, 3 Optional Expansion Board

SECURITY+ 2.0® ON-BOARD RADIO RECEIVER

- Tri-Band 310/315/390 MHz Frequency
- Up to 50 Remote Controls
(Unlimited with 811LM/813LM)

LED DIAGNOSTIC DISPLAY

- Simplifies Installation and Troubleshooting

HOMELINK® COMPATIBLE

- Version 4.0 or Higher*



*May require an external adapter depending on the model and year of your vehicle. Visit HomeLink.com for additional information.

WITH OPTIONAL
EXPANSION BOARD ONLY

QUICK CLOSE

- Closes the Gate Immediately After a Vehicle Pulls Off the Interrupt Loop

ANTI-TAILGATE

- Prevents Unauthorized Access

SUPPORT.



For Support Tools and Training Videos, Visit
LiftMasterTraining.com

For More Information on Gate Operators, Visit
LiftMaster.com/UL325Gates

To Find the Right Perimeter Access Solution for You, Visit
LiftMaster.com/Solution-Generator



Sales Support: 800.282.6225
Technical Support Center: 800.528.2806
To Order: 800.323.2276